

Techmat Supply Installation Instructions

FF109X 2 Hour Fire Rated Light Cover

Aligning the Cover

Step

Step

Step

- Inside the cover there is a half round dark grey intumescent pad which has to be positioned directly over the can.
 - Leave the beige colored area without padding directly over the junction box (see picture).

Fitting the Cover Over the Fixture Hanger Bars

- Place the Tenmat FF109X cover over the fixture.
- Cut four small slits at the bottom of the cover just deep enough to fit over the hanger bars of the fixture and enable the cover to sit flush over the drywall or ceiling tile.

Installing and Wiring the Light

- Install the light following closely the manufacturer's instructions. The wire can be fed through the side of the cover closer to the junction box.
- Due to the nature of the product, it is easy to poke the wire through the material or cut a small opening with a knife.
- Follow the light manufacturer's instructions to make proper connections. •

Final Check Step

- Check for secure fit, and make sure the cover overhangs the hanger bars.
- The bottom of the FF 109X Cover should be in full contact with the back surface of the drywall board or ceiling tile.

Ensure the cover fits your chosen light fixture.

FF109X Overall Dimensions:

- Inside Diameter 14 1/2"
- Inside Height 9 3/4"



soap and water. Consult a physician if irritation persists. Throat and Eyes

CONTAINS STONE WOOL INSULATION

If irritation occurs, flush eyes with water and/or drink water to clear throat. Do not rub the eyes. Consult a physician if irritation persists.

If irritation occurs, do not rub or scratch. Rinse under running water prior to washing with mild

WARNING: BE SURE THE ELECTRICITY TO THE SYSTEM YOU ARE WORKING ON IS TURNED

Stone fibers may cause temporary mechanical irritation to the skin, throat, nose and eyes.

PRECAUTIONS

FIRST AID

Skin

Wear long sleeve, loose fitting clothing, gloves and eye protection.

OFF; EITHER THE FUSE REMOVED OR THE CIRCUIT BREAKER SET AT OFF.

For additional information, refer to the Material Safety Data Sheet (MSDS).







(888) 573 3330

fireproofing.us

info@fireproofing.us